

TYPICAL SECTION

NOT TO SCALE

A MIN OF 1/2" AND A
MAX OF 1"

6H:1V TYP
4H:1V MAX
4H:1V MAX
TYPE "D"

6" MINIMUM BASE
REQUIRED UNDER
ALL CURBS AND
GUTTERS

DETAIL "A"

HOT MIX TO BE ABOVE THE LIP AT THE GUTTER

NOTES:

- 1. ALL BASE AND SUBGRADE WILL BE DENSITY CONTROLLED AND WILL MEET ALL SPECIFICATION REQUIREMENTS FOR THE CITY OF SAN ANGELO.
- IT IS THE GOAL OF THE CITY TO DESIGN AND CONSTRUCT A STREET SYSTEM THAT WILL HAVE A LIFE EXPECTANCY OF TWENTY YEARS WITH NORMAL MAINTENANCE. STREETS THAT ARE CONSTRUCTED IN INDUSTRIAL AREAS WHERE HEAVY LOADS ARE EXPECTED WILL REQUIRE INDIVIDUAL DESIGN PROCESSES.
- 3. 8" ENGINEERED SUBGRADE. IF STABILIZATION IS REQUIRED, THE RATE WILL BE DETERMINED ACCORDING TO TEST RESULTS.

CITY OF SAN ANGELO

URBAN RESIDENTIAL STREETS WITH ALLEYS OR SIDEWALKS January 2008 S-A-1